

Information to identify the model(s) to which the information relates to:				If function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season 'Average'.			
Indoor unit model name		<b>SRK25ZSP-W</b>		Average(mandatory)		<b>Yes</b>	
Outdoor unit model name		<b>SRC25ZSP-W</b>		Warmer(if designated)		<b>Yes</b>	
Function(indicate if present)				Colder(if designated)			
cooling		<b>Yes</b>				<b>No</b>	
heating		<b>Yes</b>					
Item				Item			
		symbol value unit				symbol value class	
Design load				Seasonal efficiency and energy efficiency class			
cooling		Pdesignc <b>2.50</b> kW		cooling		SEER <b>6.80</b> A++	
heating / Average		Pdesignh <b>2.80</b> kW		heating / Average		SCOP/A <b>4.10</b> A+	
heating / Warmer		Pdesignh <b>3.30</b> kW		heating / Warmer		SCOP/W <b>5.40</b> A+++	
heating / Colder		Pdesignh - kW		heating / Colder		SCOP/C - -	
				unit			
Declared capacity at outdoor temperature Tdesignh				Back up heating capacity at outdoor temperature Tdesignh			
heating / Average (-10°C)		Pdc <b>2.46</b> kW		heating / Average (-10°C)		elbu <b>0.34</b> kW	
heating / Warmer (2°C)		Pdc <b>3.30</b> kW		heating / Warmer (2°C)		elbu <b>0</b> kW	
heating / Colder (-22°C)		Pdc - kW		heating / Colder (-22°C)		elbu - kW	
Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj				Declared energy efficiency ratio, at indoor temperature 27(19)°C and outdoor temperature Tj			
Tj=35°C		Pdc <b>2.50</b> kW		Tj=35°C		EERd <b>3.52</b> -	
Tj=30°C		Pdc <b>1.85</b> kW		Tj=30°C		EERd <b>5.70</b> -	
Tj=25°C		Pdc <b>1.25</b> kW		Tj=25°C		EERd <b>9.36</b> -	
Tj=20°C		Pdc <b>1.10</b> kW		Tj=20°C		EERd <b>12.9</b> -	
Declared capacity for heating / Average season, at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance / Average season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C		Pdh <b>2.50</b> kW		Tj=-7°C		COPd <b>2.44</b> -	
Tj=2°C		Pdh <b>1.44</b> kW		Tj=2°C		COPd <b>3.98</b> -	
Tj=7°C		Pdh <b>1.00</b> kW		Tj=7°C		COPd <b>5.74</b> -	
Tj=12°C		Pdh <b>1.10</b> kW		Tj=12°C		COPd <b>7.30</b> -	
Tj=bivalent temperature		Pdh <b>2.50</b> kW		Tj=bivalent temperature		COPd <b>2.44</b> -	
Tj=operating limit		Pdh <b>2.40</b> kW		Tj=operating limit		COPd <b>2.06</b> -	
Declared capacity for heating / Warmer season, at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance / Warmer season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=2°C		Pdh <b>3.30</b> kW		Tj=2°C		COPd <b>2.34</b> -	
Tj=7°C		Pdh <b>2.10</b> kW		Tj=7°C		COPd <b>4.80</b> -	
Tj=12°C		Pdh <b>1.10</b> kW		Tj=12°C		COPd <b>7.30</b> -	
Tj=bivalent temperature		Pdh <b>3.30</b> kW		Tj=bivalent temperature		COPd <b>2.34</b> -	
Tj=operating limit		Pdh <b>2.40</b> kW		Tj=operating limit		COPd <b>2.06</b> -	
Declared capacity for heating / Colder season, at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance / Colder season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C		Pdh - kW		Tj=-7°C		COPd - -	
Tj=2°C		Pdh - kW		Tj=2°C		COPd - -	
Tj=7°C		Pdh - kW		Tj=7°C		COPd - -	
Tj=12°C		Pdh - kW		Tj=12°C		COPd - -	
Tj=bivalent temperature		Pdh - kW		Tj=bivalent temperature		COPd - -	
Tj=operating limit		Pdh - kW		Tj=operating limit		COPd - -	
Tj=-15°C		Pdh - kW		Tj=-15°C		COPd - -	
Bivalent temperature				Operating limit temperature			
heating / Average		Tbiv <b>-7</b> °C		heating / Average		Tol <b>-15</b> °C	
heating / Warmer		Tbiv <b>2</b> °C		heating / Warmer		Tol <b>-15</b> °C	
heating / Colder		Tbiv - °C		heating / Colder		Tol - °C	
Cycling interval capacity				Cycling interval efficiency			
for cooling		Pcycc - kW		for cooling		EERcyc - -	
for heating		Pcych - kW		for heating		COPcyc - -	
Degradation coefficient				Degradation coefficient			
cooling		Cdc <b>0.25</b> -		heating		Cdh <b>0.25</b> -	
Electric power input in power modes other than 'active mode'				Annual electricity consumption			
off mode		Poff <b>6</b> W		cooling		Qce <b>129</b> kWh/a	
standby mode		Psb <b>6</b> W		heating / Average		Qhe <b>957</b> kWh/a	
thermostat-off mode		Pto(cooling) <b>11</b> W		heating / Warmer		Qhe <b>855</b> kWh/a	
crankcase heater mode		Pto(heating) <b>15</b> W		heating / colder		Qhe - kWh/a	
crankcase heater mode		Pck <b>0</b> W					
Capacity control(indicate one of three options)				Other items			
fixed		<b>No</b>		Sound power level(indoor)		Lwa <b>57</b> dB(A)	
staged		<b>No</b>		Sound power level(outdoor)		Lwa <b>57</b> dB(A)	
variable		<b>Yes</b>		Global warming potential		GWP <b>675</b> kgCO2eq.	
				Rated air flow(indoor)		- <b>600</b> m3/h	
				Rated air flow(outdoor)		- <b>1422</b> m3/h	
Contact details for obtaining more information		Name and address of the manufacturer or of its authorised representative.					
		Mitsubishi Heavy Industries Air-Conditioning Europe, Ltd. 5 The Square, Stockley Park, Uxbridge, Middlesex, UB11 1ET, United Kingdom					