

Outdoor unit		RXC60EV1B	
Indoor unit		FTXC60EV1B	
Function		Heating season	
Охлаждане	Да	Average (mandatory)	Да
Отопление	Да	Warmer (if designated)	Да
		Colder (if designated)	Не
Item	Symbol	Value	Тяло
Design Load		Seasonal efficiency	
Охлаждане	P _{designc}	6.2	kW
heating / Average	P _{designh}	4.1	kW
heating / Warmer	P _{designh}	5.5	kW
heating / Colder	P _{designh}		kW
Обявен капацитет* за охлаждане при вътрешна температура 27(19) °C и външна температура Tj		Обявен капацитет* за охлаждане при вътрешна температура 27(19) °C и външна температура Tj	
Tj = 35 °C	P _{dc}	6.21	kW
Tj = 30 °C	P _{dc}	4.73	kW
Tj = 25 °C	P _{dc}	3.08	kW
Tj = 20 °C	P _{dc}	2.30	kW
Declared capacity* for heating / Average season , at indoor temperature 20 °C and outdoor temperature Tj		Declared coefficient of performance* / Average season, at indoor temperature 20 °C and outdoor temperature Tj	
Tj = -7 °C	P _{dh}	3.63	kW
Tj = 2 °C	P _{dh}	2.16	kW
Tj = 7 °C	P _{dh}	1.74	kW
Tj = 12 °C	P _{dh}	1.78	kW
Tj = Bivalent temperature	P _{dh}	3.63	kW
Tj = operating limit	P _{dh}	3.30	kW
Declared capacity* for heating / Warmer season , at indoor temperature 20 °C and outdoor temperature Tj		Declared coefficient of performance* / Warmer season, at indoor temperature 20 °C and outdoor temperature Tj	
Tj = 2 °C	P _{dh}	5.53	kW
Tj = 7 °C	P _{dh}	3.65	kW
Tj = 12 °C	P _{dh}	1.78	kW
Tj = Bivalent temperature	P _{dh}	5.53	kW
Tj = operating limit	P _{dh}		kW
Declared capacity* for heating / Colder season , at indoor temperature 20 °C and outdoor temperature Tj		Declared coefficient of performance* / Colder season, at indoor temperature 20 °C and outdoor temperature Tj	
Tj = -7 °C	P _{dh}		kW
Tj = 2 °C	P _{dh}		kW
Tj = 7 °C	P _{dh}		kW
Tj = 12 °C	P _{dh}		kW
Tj = Bivalent temperature	P _{dh}		kW
Tj = operating limit	P _{dh}		kW
Tj = -15 °C	P _{dh}		kW
Bivalent temperature		operating limit	
heating / Average	T _{biv}	-7	°C
heating / Warmer	T _{biv}	2	°C
heating / Colder	T _{biv}		°C
Cycling interval capacity		Cycling interval efficiency	
for cooling	P _{cyc}		kW
for heating	P _{cyc}		kW
Degradation co-efficient cooling**	C _{dc}	0.25	-
for cooling		for heating	
	EER _{cyc}		-
	COP _{cyc}		-
	C _{dh}	0.25	-
Electric power input in power models other than 'active mode'		Annual electricity consumption	
Off mode	P _{off}	0.002	kW
Standby mode	P _{sb}	0.002	kW
Thermostat-off mode	P _{TO}	0.066	kW
Crankcase heater mode	P _{CK}	0	kW
Capacity control		Other items	
fixed	N	Sound power level (indoor/outdoor)	L _{WA} 63.0 db(A)
staged	N	Global warming potential	GWP 675 kgCO ₂ eq.
variable	N	Rated air flow (indoor/outdoor)	- 20.4 / 46.2 m ³ /min
Contact details for obtaining more information		Daikin Europe N.V. Zandvoordestraat 300, B-8400 Oostende, Belgium	

* for staged capacity units, two values divided by a slash (/) will be declared in each box in the section "Declared capacity of the unit" and "Declared EER/COP" of the unit.

** if default Cd = 0.25 is chosen then (results from) cycling tests are not required. Otherwise either the heating of cooling cycling test value is required.