Information sheet (Lot.10)

This information includes the results of calculation of the seasonal energy consumption and efficiency for air conditioner in regards to ErP pursuant to the Commission Regulation(EU) No.206/2012 and No.626/2011.

Information to identify the model(s) to which the information relates to:

AIR CONDITIONER

TYPE : SINGLE SPLIT WALL MOUNTED Indoor unit(s) : RSG12KETA

Outdoor unit : ROG12KETA

BRAND : FUJI ELECTRIC

N/A = Not Applicable

Function			14/71 Hot/Ipplicable
Cooling	Yes	Average	Yes
Heating	Yes	Warmer	Yes
		Colder	No

Design load			Seasonal efficiency				
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Cooling	Pdesignc	3.4	kW	Cooling	SEER	7.30	-
Heating/Average	Pdesignh	2.5	kW	Heating/Average	SCOP/A	4.40	-
Heating/Warmer	Pdesignh	1.3	kW	Heating/Warmer	SCOP/W	5.40	-
Heating/Colder	Pdesignh	N/A	kW	Heating/Colder	SCOP/C	N/A	-

Cooling							
Declared capacity for cooling, at indoor temperature 27 (19) °C and outdoor temperature Tj			Declared energy efficiency ratio, at indoor temperature 27 (19) °C and outd	oor tempera	ature Tj		
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Tj = 35°C	Pdc	3.40	kW	Tj = 35°C	EER d	3.65	-
Tj = 30°C	Pdc	2.51	kW	Tj = 30°C	EER d	5.65	-
Tj = 25°C	Pdc	1.61	kW	Tj = 25°C	EER d	9.10	-
Tj = 20°C	Pdc	1.13	kW	Tj = 20°C	EER d	13.90	-

Heating/Average							
Declared capacity for heating/Average season, at indoor temperature 20 °C and outdoor temperature Tj			Declared coefficient of performance/Average season, at indoor temperature 20 °C and outdoor temperature Tj				
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Tj = -7°C	Pdh	2.21	kW	Tj = -7°C	COPd	3.11	-
Tj = 2°C	Pdh	1.35	kW	Tj = 2°C	COPd	4.25	-
Tj = 7°C	Pdh	0.87	kW	Tj = 7°C	COPd	5.65	-
Tj = 12°C	Pdh	0.85	kW	Tj = 12°C	COPd	6.72	-
Tj = bivalent temperature	Pdh	2.21	kW	Tj = bivalent temperature	COPd	3.11	-
Tj = operating limit	Pdh	2.14	kW	Tj = operating limit	COPd	2.71	-

Heating/Warmer							
Declared capacity for heating/Warmer season, at indoor temperature 20 °C and outdoor temperature Tj			Declared coefficient of performance/Warmer season, at indoor temperature 20 °C and outdoor temperature Tj				
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Tj = 2°C	Pdh	1.34	kW	Tj = 2°C	COPd	4.25	-
Tj = 7°C	Pdh	0.86	kW	Tj = 7°C	COPd	5.55	-
Tj = 12°C	Pdh	0.85	kW	Tj = 12°C	COPd	6.64	-
Tj = bivalent temperature	Pdh	1.34	kW	Tj = bivalent temperature	COPd	4.25	-
Tj = operating limit	Pdh	2.14	kW	Tj = operating limit	COPd	2.71	-

Heating/Colder								
Declared capacity for heating/Colder season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance/Colder season, at indoor temperature 20 °C and outdoor temperature Tj				
Item Symbol Value Unit			Item	Symbol	Value	Unit		
Tj = -7°C	Pdh	N/A	kW	Tj = -7°C	COPd	N/A	-	
Tj = 2°C	Pdh	N/A	kW	Tj = 2°C	COPd	N/A	-	
Tj = 7°C	Pdh	N/A	kW	Tj = 7°C	COP d	N/A	-	
Tj = 12°C	Pdh	N/A	kW	Tj = 12°C	COP d	N/A	-	
Tj = bivalent temperature	Pdh	N/A	kW	Tj = bivalent temperature	COP d	N/A	-	
Tj = operating limit	Pdh	N/A	kW	Tj = operating limit	COP d	N/A	-	
Tj=-15°C	Pdh	N/A	kW	Tj = -15°C	COP d	N/A	-	

Bivalent temperature			Operating limit temperature				
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Heating/Average	Tbiv	-7	°C	Heating/Average	Tol	-15	°C
Heating/Warmer	Tbiv	2	°C	Heating/Warmer	Tol	-15	°C
Heating/Colder	Tbiv	N/A	°C	Heating/Colder	Tol	N/A	°C

Cycling interval capacity			Cycling interval efficiency				
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
For cooling	Pcycc	N/A	kW	For cooling	EERcyc	N/A	-
For heating	Pcych	N/A	kW	For heating	COPcyc	N/A	-
Degradation coefficient cooling	Cdc	0.25	-	Degradation coefficient heating	Cdh	0.25	-

Electric power input in power modes other than 'active mode'				Annual electricity consumption				
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit	
Off mode (Cooling/Heating)	P _{OFF}	5.0/5.0	W	Cooling	Q _{CE}	163	kWh/a	
Standby mode (Cooling/Heating)	P _{SB}	5.0/5.0	W	Heating/Average	Q_{HE}	795	kWh/a	
Thermostat-off mode (Cooling/Heating)	P _{TO}	1.0/11.0	W	Heating/Warmer	Q_{HE}	347	kWh/a	
Crankcase heater mode (Cooling/Heating)	P _{CK}	0.0/0.0	W	Heating/Colder	Q _{HE}	N/A	kWh/a	

Capacity control		Other items				
Item	Y/N	Item	Symbol	Value	Unit	
Fixed	No	Sound power level (Indoor/Outdoor)	L _{WA}	55.0/65.0	dB(A)	
Staged	No	Global warming potential	GWP	675	kgCO ₂ eq.	
Variable	Yes	Rated air flow (Indoor/Outdoor)	-	700/1700	m³/h	

	FUJITSU GENERAL LIMITED
Contact details for obtaining more information	3-3-17, Suenaga, Takatsu-ku, Kawasaki, 213-8502, Japan

V20121214