

Product fiche according to Commission Delegated Regulation (EU) 626/2011

MODEL	OUTDOOR UNIT	ROG07KMTA		ROG09KMTA		ROG12KMTA		ROG14KMTA	
	INDOOR UNIT	RSG07KMTA RSG07KMTB		RSG09KMTA RSG09KMTB		RSG12KMTA RSG12KMTB		RSG14KMTA RSG14KMTB	
		COOLING	HEATING	COOLING	HEATING	COOLING	HEATING	COOLING	HEATING
SOUND POWER LEVEL	OUTDOOR UNIT [dB(A)]	61	61	61	62	65	65	65	66
	INDOOR UNIT [dB(A)]	54	56	55	57	55	58	57	59
REFRIGERANT/GLOBAL WARMING POTENTIAL		R32 / 675 (IPCC AR4) ^(*)							
SEASONAL ENERGY EFFICIENCY RATIO/ SEASONAL COEFFICIENT OF PERFORMANCE		7.4	4.1	7.4	4.1	7.3	4.4	6.9	4.1
ENERGY EFFICIENCY CLASS		A++	A+	A++	A+	A++	A+	A++	A+
ANNUAL ENERGY CONSUMPTION (Q _{CE})(Q _{HE}) [kWh/a]		95 ^(*)	785 ^(*)	118 ^(*)	819 ^(*)	163 ^(*)	795 ^(*)	213 ^(*)	1367 ^(*)
P _{design} [kW]		2.0 (35 °C)	2.3 (-10 °C)	2.5 (35 °C)	2.4 (-10 °C)	3.4 (35 °C)	2.5 (-10 °C)	4.2 (35 °C)	4.0 (-10 °C)
BACKUP HEATER CAPACITY/ DECLARED CAPACITY [kW]		—	0.28/ 2.02	—	0.33/ 2.07	—	0.31/ 2.19	—	0.47/ 3.53

NOTES

(*) Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to [675]. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be [675] times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

(*) Energy consumption "Q_{CE}" kWh per year based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

(*) Energy consumption "Q_{HE}" kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

Specifications

MODEL	OUTDOOR UNIT	ROG07KMTA		ROG09KMTA		ROG12KMTA		ROG14KMTA	
	INDOOR UNIT	RSG07KMTA RSG07KMTB		RSG09KMTA RSG09KMTB		RSG12KMTA RSG12KMTB		RSG14KMTA RSG14KMTB	
TYPE		WALL MOUNTED SINGLE SPLIT / HEAT PUMP							
MAX. PRESSURE	HIGH / DISCHARGE [bar(MPa)]	- (4.20)							
	LOW / SUCTION [bar(MPa)]	- (1.18)						- (1.21)	
MANUFACTURING DATE		Refer to the rating label							
POWER RESOURCE		1φ 230 V ~ 50 Hz							
		COOLING	HEATING	COOLING	HEATING	COOLING	HEATING	COOLING	HEATING
CAPACITY [kW]		2.00	2.50	2.50	2.80	3.40	4.00	4.20	5.40
POWER INPUT [kW]		0.450	0.555	0.630	0.620	0.935	0.960	1.220	1.410
CURRENT [A]		2.6	3.0	3.4	3.4	4.8	5.1	5.8	6.8
MAX. CURRENT [A]		6.5	9.0	6.5	9.0	6.5	9.0	6.5	9.0
ENERGY EFFICIENCY RATIO/ COEFFICIENT OF PERFORMANCE [kW/kW]		4.43	4.52	3.97	4.52	3.65	4.17	3.44	3.83
DIMENSION (H×W×D)	OUTDOOR UNIT [mm]	541 × 663 × 290						542 × 799 × 290	
	INDOOR UNIT [mm]	270 × 834 × 215							
WEIGHT	OUTDOOR UNIT [kg]	23				25		31	
	INDOOR UNIT [kg]	10							
REFRIGERANT CHARGE (Tons - CO ₂ equivalent) [kg] (t-CO ₂ eq)		0.60 (0.405)				0.70 (0.473)		0.85 (0.574)	

- For more information, visit our web site at: www.fujitsu-general.com
- For spare parts inquiry, consult the store that you purchased the product.
- Sound pressure level : less than 70 dB(A) by according to IEC 704-1.

OPERATING RANGE	INDOOR	OUTDOOR
COOLING/DRY [°C]	18 to 32	-10 to 46
HEATING [°C]	16 to 30	-15 to 24
HUMIDITY [%]	80 or less	—

- If the air conditioner is operated under the conditions except the permissible temperature range, the air conditioner may stop because of the automatic protection circuit working.
- Depending on the operating conditions, the heat exchanger may freeze during the Cooling or Dry mode and it may cause water leakage and other damage.
- If the unit is used for long periods under high-humidity conditions, condensation may form on the surface of the indoor unit, and drip onto the floor or other objects underneath.

[Original instructions]



PART No. 9320700829-03 (En)

Fuji Furukawa Engineering & Construction Co.Ltd.